



TI-34 MultiView™ Scientific Calculator Guidebook

Important information

Texas Instruments makes no warranty, either express or implied, including but not limited to any implied warranties of merchantability and fitness for a particular purpose, regarding any programs or book materials and makes such materials available solely on an "as-is" basis. In no event shall Texas Instruments be liable to anyone for special, collateral, incidental, or consequential damages in connection with or arising out of the purchase or use of these materials, and the sole and exclusive liability of Texas Instruments, regardless of the form of action, shall not exceed the purchase price of this product. Moreover, Texas Instruments shall not be liable for any claim of any kind whatsoever against the use of these materials by any other party.

MathPrint, APD, Automatic Power Down, EOS, and MultiView are trademarks of Texas Instruments Incorporated.

Copyright © 2019 Texas Instruments Incorporated

Contents

Getting Started	1
Examples	1
Switching the Calculator On and Off	1
Display Contrast	1
Home Screen	1
2nd Functions	2
Modes	2
Menus	4
Scrolling	6
Answer Toggle	7
Last Answer	8
Order of Operations	8
Clearing and Correcting	10
Math Operations	10
Memory and Stored Variables	12
Math Functions	15
Integer Divide	15
Fractions	15
Percentages	17
x10n Key	18
Powers, Radicals, and Reciprocals	19
Pi	20
Angle Menu	21
Trigonometry	23
Logarithms and Exponential Functions	25
Statistics	26
Probability	30
Math Tools	33
Data Editor and List Conversions	33
Stored Operations (op)	35
Reference Information	37
Errors	37
Battery Information	38
In Case of Difficulty	39
General Information	40

Getting Started

Examples

Each section is followed by instructions for keystroke examples that demonstrate the TI-34 MultiView™ functions.

Examples assume all default settings, as shown in the Modes section.

For more activities and examples, see the TI-34 MultiView Teacher Guide available at education.ti.com/guides.

Switching the Calculator On and Off

[on] turns on the TI-34 MultiView™ calculator **[2nd] [off]** turns it off. The display is cleared, but the history, settings, and memory are retained.

The APD™ (Automatic Power Down™) feature turns off the TI-34 MultiView™ calculator automatically if no key is pressed for about 5 minutes. Press **[on]** after APD. The display, pending operations, settings, and memory are retained.

Display Contrast

The brightness and contrast of the display can depend on room lighting, battery freshness, and viewing angle.

To adjust the contrast:

1. Press and release the **[2nd]** key.
2. Press **[+]** (to darken the screen) or **[-]** (to lighten the screen).

Home Screen






On the Home screen, you can enter mathematical expressions and functions, along with other instructions. The answers are displayed on the Home screen. The TI-34 MultiView screen can display a maximum of four lines with a maximum of 16 characters per line. For entries and expressions of more than 16 characters, you can scroll left and right (**[←]** and **[→]**) to view the entire entry or expression.

In the MathPrint™ mode, you can enter up to four levels of consecutive nested functions and expressions, which include fractions, square roots, exponents with \wedge , $x\sqrt{\quad}$, and x^2 .

When you calculate an entry on the Home screen, depending upon space, the answer is displayed either directly to the right of the entry or on the right side of the next line.






Special indicators may display on the screen to provide additional information concerning functions or results.

Indicator	Definition
2ND	2nd function.
FIX	Fixed-decimal setting. (See Modes section.)

SCI	Scientific notation. (See Modes section.)
DEG, RAD	Angle mode (degrees or radians). (See Modes section.)
L1, L2, L3	Displays above the lists in Data Editor and List Conversions.
	The TI-34 MultiView™ calculator is performing an operation.
↑ ↓	An entry is stored in memory before and/or after the active screen. Press  and  to scroll.
← →	An entry or menu displays beyond 16 digits. Press  and  to scroll. (See Scrolling for more information.)










2nd Functions




Most keys can perform two functions. The primary function is indicated on the key and the secondary function is displayed above it. Press  to activate the secondary function of a given key. Notice that **2nd** appears as an indicator on the screen. To cancel it before entering data, press  again. For example, **3**   **125**  calculates the cube root of 125 and returns the result, 5.

Modes



Use  to choose modes. Press     to choose a mode, and  to select it. Press  or   to return to the Home screen and perform your work using the chosen mode settings.

Default settings are shown.



DEG RAD Sets the angle mode to degrees or radians.

NORM SCI Sets the numeric notation mode. Numeric notation modes affect only the display of results, and not the accuracy of the values stored in the unit, which remain maximal.

NORM displays results with digits to the left and right of the decimal, as in 123456.78.

SCI expresses numbers with one digit to the left of the decimal and the appropriate power of 10, as in 1.2345678×10^5 (which is the same as 123456.78).

Note: $\boxed{\times 10^n}$ is a shortcut key to enter a number in scientific notation format. The result displays in the numeric notation format set in mode.

Note: In some restricted environments (for example, data editor and the $\boxed{2nd}$ [recall] menu), the TI-34 MultiView™ calculator may display **E** instead of $\times 10^n$.

FLOAT 0123456789 Sets the decimal notation mode.

FLOAT (floating decimal point) displays up to 10 digits, plus the sign and decimal.

0123456789 (fixed decimal point) specifies the number of digits (0 through 9) to display to the right of the decimal.

CLASSIC MATHPRINT

CLASSIC mode displays inputs and outputs in a single line.

MATHPRINT mode displays most inputs and outputs in textbook format. Choose the MathPrint™ mode for better visual confirmation that math expressions have been entered correctly and to better reinforce the correct math notation.

Note: Switching the mode between Classic and MathPrint clears calculator history and the stored operations (**op1** or **op2**) value.





Un/d n/d Determines how fractional results are displayed. Un/d displays results as a mixed number, if applicable. n/d displays results as a simple fraction.

MANSIMP AUTOSIMP Determine whether or not a fractional result will be simplified automatically.

MANSIMP The user simplifies fractions manually step-by-step. \downarrow next to the resulting fraction signifies that the fraction is not yet in simplest form. See Fractions, $\boxed{\rightarrow \text{simp}}$ for details.

AUTOSIMP The calculator automatically simplifies fractional results to the lowest terms.

Example of Classic and MathPrint Modes

Classic mode	MathPrint mode
Sci 	Sci 
Float mode and answer toggle key. 	Float mode and answer toggle key. 
Fix 2	Fix 2 and answer toggle key.

Classic mode	MathPrint mode
$2\pi \quad \text{DEG} \quad \text{↕} \quad 6.28$	$2\pi \quad \text{DEG} \quad \text{↕} \quad 2\pi$ $2\pi \text{↕} \quad 6.28$
n/d Un/d $1/2+3/4 \quad \text{DEG} \quad \text{↕} \quad 1\frac{1}{4}$ $1\frac{1}{4} \text{↕} \text{U} \quad 5/4$	$\frac{1}{2} + \frac{3}{4} \quad \text{DEG} \quad \text{↕} \quad 1\frac{1}{4}$ $1\frac{1}{4} \text{↕} \text{U} \quad \frac{5}{4}$
Mansimp $8/16 \quad \text{DEG} \quad \text{↕} \quad 8/16$ $8/16 \text{↕} \text{SIMP} \quad 8 \quad 1/2$	$\frac{8}{16} \quad \text{DEG} \quad \text{↕} \quad \frac{8}{16}$ $\frac{8}{16} \text{↕} \text{SIMP} \quad 8 \quad \frac{1}{2}$
Autosimp $1/4+3/12 \quad \text{DEG} \quad \text{↕} \quad 1/2$	$\frac{1}{4} + \frac{3}{12} \quad \text{DEG} \quad \text{↕} \quad \frac{1}{2}$
Exponent example $2^5 \quad \text{DEG} \quad \text{↕} \quad 32$	$2^5 \quad \text{DEG} \quad \text{↕} \quad 32$
Cube root example $\sqrt[3]{64} \quad \text{DEG} \quad \text{↕} \quad 4$	$\sqrt[3]{64} \quad \text{DEG} \quad \text{↕} \quad 4$

Menus

Certain keys display menus: $\boxed{\text{prb}}$, $\boxed{2\text{nd}}$ [angle], $\boxed{2\text{nd}}$ [log], $\boxed{2\text{nd}}$ [trig], $\boxed{\text{math}}$, $\boxed{\text{data}}$ $\boxed{\text{data}}$, $\boxed{2\text{nd}}$ [stat], $\boxed{2\text{nd}}$ [reset], $\boxed{2\text{nd}}$ [recall], and $\boxed{2\text{nd}}$ [clear var].

Press \ominus and \odot to scroll and select a menu item, or press the corresponding number next to the menu item. To return to the previous screen without selecting the item, press $\boxed{\text{clear}}$. To exit a menu or application and return to the Home screen, press $\boxed{2\text{nd}}$ [quit].

The menu chart shows the menu keys and the menus they display.

prb		2nd [angle]	
PRB	RAND	DMS	R ◀ ▶ P
1: nPr 2: nCr 3: !	1: rand 2: randint(1: ° 2: ' 3: " 4: r 5: ▶ DMS	1: R ▶ Pr(2: R ▶ Pθ(3: P ▶ Rx(4: P ▶ Ry(

2nd [log]		2nd [trig]
LOG	LN	TRIG
1: log(2: 10^(1: ln(2: e^(1: sin(2: cos(3: tan(4: sin ⁻¹ (5: cos ⁻¹ (6: tan ⁻¹ (

math	
MATH	NUM
1: lcm(2: gcd(3: ³ 4: ³ √(1: abs(2: round(3: iPart(4: fPart(5: min(6: max(7: remainder(

data **data**

Press once to display the Data editor screen. Press again to display the menu.

CLEAR	CNVRSN
1: Clear L1 2: Clear L2 3: Clear L3 4: Clear ALL	1: Add/Edit Cnvrs 2: Clear L1 Cnvrs 3: Clear L2 Cnvrs 4: Clear L3 Cnvrs 5: Clear ALL

Press **[data]** while you are in the Add/Edit Conversion option of the CNVRSN menu to display this menu:

Ls

- 1: L1
 - 2: L2
 - 3: L3
-

[2nd] [stat]

STATS

- 1: 1-Var Stats
 - 2: 2-Var Stats
 - 3: StatVars*
-

* This menu option displays after you calculate 1-var or 2-var stats:

StatVars

- 1: n
- 2: \bar{x}
- 3: Sx

Etc. See Statistics values for a full list.

[2nd] [reset]	[2nd] [recall]	[2nd] [clear var]
Reset	Recall Var	Clear Var
1: No 2: Yes	1: x = 2: y = 3: z = 4: t = 5: a = 6: b = 7: c =	1: Yes 2: No

Scrolling









Press **[left]** or **[right]** to scroll entries on the Home screen and to navigate in menus. Press **[2nd] [left]** or **[2nd] [right]** to move the cursor directly to the beginning or end of the current expression.

⊖ and ⊕ moves the cursor up and down through menu items, entries in Data editor, and previous entries on the Home screen. You can reuse a previous entry by pressing **enter** to paste it on the bottom line, and then evaluating a new expression.

2nd ⊖ moves the cursor to the top entry of the active column in Data editor, or to the previous entry on the Home screen. Press **2nd** ⊖ again to move the cursor to the oldest entry on the Home screen.


2nd ⊕ moves the cursor to the first blank row of the active column in Data editor, or below the last entry on the Home screen.

Examples

Scroll	1 + 1 enter	
	2 + 2 enter	
	3 + 3 enter	
	4 + 4 enter	
	⊖ ⊖ ⊖ ⊖ enter	
	+ 2 enter	

Answer Toggle



Press the  key to toggle the display result between fraction and decimal answers, and exact pi and decimal.

Example

Answer toggle	2 π enter	2π DEG \leftrightarrow
	\leftrightarrow	2π DEG \leftrightarrow $2\pi^{\leftrightarrow}$ 6.283185307

Last Answer

$\boxed{2nd}$ [ans]

The most recently calculated result is stored to the variable **ans**. **ans** is retained in memory, even after the TI-34 MultiView™ calculator is turned off. To recall the value of **ans**:

- Press $\boxed{2nd}$ [ans] (**ans** displays on the screen), or
- Press any operations key (\oplus , \ominus , and so forth) as the first part of an entry. **ans** and the operator are both displayed.

Examples

ans	3 \times 3 enter	3×3 DEG \leftrightarrow 9
	\times 3 enter	3×3 DEG \leftrightarrow ans \times 3 9 27
	3 $\boxed{2nd}$ [\sqrt{x}] $\boxed{2nd}$ [ans] enter	3×3 DEG \leftrightarrow ans \times 3 9 $\sqrt{\text{ans}}$ 27 3

Order of Operations

The TI-34 MultiView™ calculator uses Equation Operating System (EOS™) to evaluate expressions. Within a priority level, EOS evaluates functions from left to right and in the following order.

1st	Expressions inside parentheses.
2nd	Functions that need a) and precede the argument, such as sin , log , and all R\blacktrianglerightP menu items.

3rd	Fractions.
4th	Functions that are entered after the argument, such as x^2 and angle unit modifiers.
5th	<p>Exponentiation (^) and roots (\sqrt{x}).</p> <p>Note: In Classic mode, exponentiation using \square is evaluated from left to right. The expression $2^3 \wedge 2$ is evaluated as $(2^3)^2$, with a result of 64.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> $2^3 \wedge 2$ DEG \leftrightarrow 64 </div> <p>In MathPrint™ mode, exponentiation using \square is evaluated from right to left. The expression $2^3 \wedge 2$ is evaluated as $2^{(3^2)}$, with a result of 512.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> 2^{3^2} DEG \leftrightarrow 512 </div> <p>The TI-34 MultiView™ calculator evaluates expressions entered with \square from left to right in both Classic and MathPrint modes.</p>
6th	Negation (-).
7th	Permutations (nPr) and combinations (nCr).
8th	Multiplication, implied multiplication, division.
9th	Addition and subtraction.
10th	Conversions (n/d \blacktriangleright Un/d , f \blacktriangleright d , \blacktriangleright DMS).
11th	\square completes all operations and closes all open parentheses.

Examples

$+ \times \div -$	60 \square 5 \times \square 12 \square	$60+5 \times 12$ DEG \leftrightarrow 0
$(-)$	1 \square \square 8 \square 12 \square	$1+ -8+12$ DEG \leftrightarrow 5

()	$\sqrt{}$ 9 + 16 enter	$\sqrt{9+16}$ 5
	4 \times ((2 + 3)) enter	$4 \times (2+3)$ 20
	4 ((2 + 3)) enter	$4(2+3)$ 20
\wedge and $\sqrt[x]{}$	$\sqrt{}$ 3 \wedge 2 enter + 4 $\sqrt{}$ 2 enter	$\sqrt{3^2+4^2}$ 5

Clearing and Correcting

clear	<p>Clears characters and error messages.</p> <p>Clears characters on the entry line, then clears the display when you press clear again. Scroll up to clear entries in history.</p> <p>Backs up one screen in applications.</p>
delete	Deletes the character at the cursor.
2nd [insert]	Inserts a character at the cursor.
2nd [clear var]	Clears variables x , y , z , t , a , b , and c .
2nd [reset] 2	<p>Resets the TI-34 MultiView™ calculator.</p> <p>Returns unit to default settings; clears memory variables, pending operations, all entries in history, functions in applications, and statistical data; clears stored operations (op1 or op2), and ans.</p>

Math Operations

math







math displays a menu with two submenus. Some functions require you to enter 2 values, numbers, or expressions that equal or return a number. 2nd [,] separates two values.

MATH submenu:

$\text{lcm}(n_1, n_2)$	Finds the least common multiple (lcm) or
$\text{gcd}(n_1, n_2)$	greatest common divisor (gcd) of two values, n_1



	and n_2 , which are positive integers.
n^3	Calculates the cube of n .
$\sqrt[3]{n}$	Calculates the cube root of n .
NUM submenu:	
abs(n)	Displays absolute value of n .
round(n, $digits$)	Rounds n to specified number of $digits$.
iPart(n) fPart(n)	Returns only the integer part (iPart) or fractional (decimal) part (fPart) of n .
min(n_1, n_2) max(n_1, n_2)	Returns the minimum (min) or maximum (max) of two values, n_1 and n_2 .
remainder(n_1, n_2)	Returns the remainder resulting from the division of 2 values, n_1 by n_2 .

Examples

abs	$\boxed{\text{math}} \rightarrow \boxed{1} \boxed{(-)} \boxed{2} \boxed{\frac{\square}{\square}}$ $\boxed{3} \boxed{\text{enter}}$	
round	$\boxed{\text{math}} \rightarrow \boxed{2} \boxed{\pi} \boxed{2\text{nd}}$ $\boxed{[,] \boxed{3} \boxed{]}} \boxed{\text{enter}}$	
iPart, fPart	$\boxed{\text{math}} \rightarrow \boxed{3}$ $\boxed{23.45} \boxed{]}} \boxed{\text{enter}}$ $\boxed{\text{math}} \rightarrow \boxed{4}$ $\boxed{23.45} \boxed{]}} \boxed{\text{enter}}$	
$\sqrt[3]{n}, n^3$	$\boxed{2} \boxed{\text{math}} \boxed{3} \boxed{\text{enter}}$	
	$\boxed{\text{math}} \boxed{4}$ $\boxed{8} \boxed{\text{enter}}$	
remainder	$\boxed{\text{math}} \rightarrow \boxed{7}$ $\boxed{10} \boxed{2\text{nd}} \boxed{[,] \boxed{6} \boxed{]}}$ $\boxed{\text{enter}}$	

Problem

Find the least common multiple of 30 and 84 using prime factorization by hand. Verify your work using the calculator.

$2 \times 3 \times 5$ enter $2 \times^2 \times 3 \times 7$ enter	
$2 \times^2 \times 3 \times 5 \times 7$ enter math 1 30 2nd [,] 84) enter	

The lcm (30, 84) is 420.

Memory and Stored Variables

x^{yzt} **sto** **2nd** [recall] **2nd** [clear var]

The TI-34 MultiView™ calculator has 7 memory variables—**x**, **y**, **z**, **t**, **a**, **b**, and **c**. You can store a real number or an expression that results in a real number to a memory variable.



sto lets you store values to variables. Press **sto** to store a variable, and press x^{yzt} to select the variable to store. Press **enter** to store the value in the selected variable. If this variable already has a value, that value is replaced by the new one.

x^{yzt} accesses the variables. Press this key multiple times to choose **x**, **y**, **z**, **t**, **a**, **b**, or **c**. You can also use x^{yzt} to recall the stored values for these variables. The name of the variable is inserted into the current entry, but the value assigned to the variable is used to evaluate the expression.

2nd [recall] recalls the values of variables. Press **2nd** [recall] to display a menu of variables and their stored values. Select the variable you want to recall and press **enter**. The value assigned to the variable is inserted into the current entry and used to evaluate the expression.

2nd [clear var] clears all variable values. Press **2nd** [clear var] and select **1: Yes** to clear all variable values.

Examples

Clear Var	2nd [clear var] 1	
Store	15 sto x^{yzt}	

	enter	$15 \rightarrow x$ DEG + 15
Recall	2nd [recall]	Recall Var DEG $1 \rightarrow x = 15$ $2 \rightarrow y = 0$ $3 \rightarrow z = 0$
	enter x^2 enter	$15 \rightarrow x$ DEG ++ 15 15^2 225
	sto $x^{y \pm 1}$ $x^{y \pm 1}$	$15 \rightarrow x$ DEG + 15 15^2 225 $\text{ans} \rightarrow y$
	enter	DEG ++ $15 \rightarrow x$ 15 15^2 225 $\text{ans} \rightarrow y$ 225
	$x^{y \pm 1}$ $x^{y \pm 1}$	DEG + $15 \rightarrow x$ 15 15^2 225 $\text{ans} \rightarrow y$ 225 y
	enter \div 4 enter	DEG ++ 15^4 225 $\text{ans} \rightarrow y$ 225 y 225 $\text{ans} \div 4$ 56.25

Problem

In a gravel quarry, two new excavations have been opened. The first one measures 350 meters by 560 meters, the second one measures 340 meters by 610 meters. What volume of gravel does the company need to extract from each excavation to reach a depth of 150 meters? To reach 210 meters?

350 \times 560 sto $x^{y \pm 1}$ enter	DEG ++ $350 \times 560 \rightarrow x$ 196000
340 \times 610 sto $x^{y \pm 1}$ $x^{y \pm 1}$ enter	DEG ++ $350 \times 560 \rightarrow x$ 196000 $340 \times 610 \rightarrow y$ 207400

150 <input type="button" value="x"/> <input type="button" value="2nd"/> <input type="button" value="recall"/>	<div style="text-align: right;">DEG</div> Recall Var 1: x=196000 2: y=207400 3: z=0
<input type="button" value="enter"/> <input type="button" value="enter"/>	<div style="text-align: right;">DEG ↔</div> 340×610→y 207400 150×196000 29400000
210 <input type="button" value="x"/> <input type="button" value="2nd"/> <input type="button" value="recall"/> <input type="button" value="enter"/> <input type="button" value="enter"/>	<div style="text-align: right;">DEG ↔</div> 150×196000 29400000 210×196000 41160000
150 <input type="button" value="x"/> <input type="button" value="x<sup>yzt</sup><sub>abc</sub>"/> <input type="button" value="x<sup>yzt</sup><sub>abc</sub>"/> <input type="button" value="enter"/>	<div style="text-align: right;">DEG ↔</div> 29400000 210×196000 41160000 150×y 31110000
210 <input type="button" value="x"/> <input type="button" value="x<sup>yzt</sup><sub>abc</sub>"/> <input type="button" value="x<sup>yzt</sup><sub>abc</sub>"/> <input type="button" value="enter"/>	<div style="text-align: right;">DEG ↔</div> 210×196000 41160000 150×y 31110000 210×y 43554000

For the first excavation: The company needs to extract 29.4 million cubic meters to reach a depth of 150 meters, and to extract 41.16 million cubic meters to reach a depth of 210 meters.

For the second excavation: The company needs to extract 31.11 million cubic meters to reach a depth of 150 meters, and to extract 43.554 million cubic meters to reach a depth of 210 meters.


Math Functions

Integer Divide

$\boxed{2\text{nd}}$ $\boxed{[\text{int}\div]}$



$\boxed{2\text{nd}}$ $\boxed{[\text{int}\div]}$ divides 2 positive integers and displays the quotient, q , and the remainder, r . Only the quotient is stored to **ans**.

Example

Int divide	$\boxed{17}$ $\boxed{2\text{nd}}$ $\boxed{[\text{int}\div]}$ $\boxed{3}$ $\boxed{\text{enter}}$	
------------	---	---

Problem

How many hours, minutes, and seconds are there in 17589 seconds?

$\boxed{17589}$ $\boxed{2\text{nd}}$ $\boxed{[\text{int}\div]}$ $\boxed{60}$ $\boxed{\text{enter}}$	
$\boxed{2\text{nd}}$ $\boxed{[\text{ans}]}$ $\boxed{2\text{nd}}$ $\boxed{[\text{int}\div]}$ $\boxed{60}$ $\boxed{\text{enter}}$	

17589 seconds equals 4 hours, 53 minutes, and 9 seconds.

Fractions

$\boxed{\frac{n}{d}}$ $\boxed{U\frac{n}{d}}$ $\boxed{2\text{nd}}$ $\boxed{[\frac{n}{d} \leftrightarrow U\frac{n}{d}]}$ $\boxed{\text{simp}}$ $\boxed{2\text{nd}}$ $\boxed{[f \leftrightarrow d]}$

In the MathPrint™ mode, fractions with $\boxed{\frac{n}{d}}$ can include operation keys ($\boxed{+}$, $\boxed{\times}$, etc.) and most function keys ($\boxed{x^2}$, $\boxed{\%}$, etc.).

In Classic mode, fractions with $\boxed{\frac{n}{d}}$ do not allow operation keys, functions, or complex fractions in the numerator or denominator.

Note: In Classic mode and Data editor, use $\boxed{\div}$ to perform complex division problems.

Calculations using fractions can display fraction or decimal results, depending on input.

- $\boxed{\frac{n}{d}}$ enters a simple fraction. Pressing $\boxed{\frac{n}{d}}$ before or after a number can result in different behavior. Entering a number before pressing $\boxed{\frac{n}{d}}$ makes that number the numerator.

To enter fractions with operators, press $\boxed{\frac{n}{d}}$ before you enter a number (in MathPrint mode only).

In MathPrint mode, press \ominus between the entry of the numerator and the denominator.

In Classic mode, press $\frac{\square}{\square}$ between the entry of the numerator and the denominator.

- $\frac{\square}{\square}$ enters a mixed number. Press $\frac{\square}{\square}$ between the entry of the unit and the numerator, and press \ominus between the entry of the numerator and the denominator.
- $\text{▶simp } n \text{▶enter}$ simplifies a fraction by the factor n specified. The entry n must be a positive integer.
- ▶simp▶enter automatically simplifies a fraction using the lowest common prime factor. The factor displays. Repeatedly press ▶simp▶enter to simplify the fraction to its lowest terms.
- $2\text{nd} \left[\frac{\square}{\square} \leftrightarrow \text{U}\frac{\square}{\square} \right]$ converts between simple fraction and mixed number form.
- $2\text{nd} [f \leftrightarrow d]$ converts results between fractions and decimals.

From mode , you can select

- **ManSimp** (default) The user simplifies fractions manually step-by-step. \downarrow next to the resulting fraction signifies that the fraction is not yet in simplest form.
- **AutoSimp** The calculator automatically simplifies fractional results to the lowest terms.

Examples of Classic mode

n/d, Un/d	$3 \left[\frac{\square}{\square} \right] 4 \left[+ \right] 1 \left[\text{U}\frac{\square}{\square} \right] 7 \left[\frac{\square}{\square} \right]$ 12▶enter	$\begin{array}{r} 3/4+1\text{U}7/12 \\ \downarrow 2\text{U}4/12 \end{array}$
Simp	$\text{▶simp } 2 \text{▶enter}$	$\begin{array}{r} 3/4+1\text{U}7/12 \\ \downarrow 2\text{U}4/12 \\ 2\text{U}4/12 \text{▶simp } 2 \\ \downarrow 2\text{U}2/6 \end{array}$
	$\text{▶simp } 2 \text{▶enter}$	$\begin{array}{r} 2\text{U}4/12 \text{▶simp } 2 \\ \downarrow 2\text{U}2/6 \\ 2\text{U}2/6 \text{▶simp } 2 \\ 2\text{U}1/3 \end{array}$
n/d \leftrightarrow Un/d	$9 \left[\frac{\square}{\square} \right] 2 \left[2\text{nd} \left[\frac{\square}{\square} \leftrightarrow \text{U}\frac{\square}{\square} \right] \right]$ enter	$\begin{array}{r} \downarrow 2\text{U}2/6 \\ 2\text{U}2/6 \text{▶simp } 2 \\ 2\text{U}1/3 \\ 9/2 \text{▶}\% \text{▶U}\% \\ 4\text{U}1/2 \end{array}$
f \leftrightarrow d	$4 \left[\text{U}\frac{\square}{\square} \right] 1 \left[\frac{\square}{\square} \right] 2 \left[2\text{nd} \left[f \leftrightarrow d \right] \right]$ enter	$\begin{array}{r} 2\text{U}2/6 \text{▶simp } 2 \\ 2\text{U}1/3 \\ 4\text{U}1/2 \\ 4\text{U}1/2 \text{▶f} \leftrightarrow \text{d} \\ 4.5 \end{array}$

Examples of MathPrint™ mode

n/d, Un/d	$\frac{3}{4} \ominus 4 \oplus 1$ $\frac{7}{12}$ \ominus 12 enter	$\frac{3}{4} + 1\frac{7}{12}$ $\downarrow 2\frac{4}{12}$
Simp	▶simp 2 enter	$2\frac{4}{12} \text{▶simp } 2$ $\downarrow 2\frac{2}{6}$
	▶simp 2 enter	$2\frac{2}{6} \text{▶simp } 2$ $2\frac{1}{3}$
n/d \leftrightarrow Un/d	9 $\frac{2}{3}$ \oplus 2 \oplus $\frac{1}{3} \leftrightarrow \frac{2}{3}$ enter	$2\frac{2}{6} \text{▶simp } 2$ $\frac{2}{3} \text{▶}\% \leftrightarrow \frac{1}{3}$ $4\frac{1}{2}$
f \leftrightarrow d	4 $\frac{1}{2}$ \ominus 2 \oplus 2nd [f \leftrightarrow d] enter	$\frac{3}{2} \text{▶}\% \leftrightarrow \frac{1}{2}$ $4\frac{1}{2} \text{▶f}\leftrightarrow\text{d}$ 4.5
Examples (MathPrint™ mode only)	$\frac{1.2}{4} \oplus 1.3 \ominus$ enter	$\frac{1.2 + 1.3}{4}$ 0.625
(MathPrint™ mode only)	$\frac{(-5 + \sqrt{5^2 - 4(1)(6)}}{2(1)}$ 1 6 \ominus 2 enter	$\frac{-5 + \sqrt{5^2 - 4(1)(6)}}{2(1)}$ -2

Percentages

$\%$ 2nd [%]

To perform a calculation involving a percentage, enter a number and press $\%$ to append the % sign.

To express a value as a percentage, press 2nd [%] after the value.

Example

2 $\%$ \times 150 enter	$2\% \times 150$ 3
------------------------------------	-----------------------

1 $\frac{\square}{\square}$ 5 \downarrow [2nd] [%] [enter]	$\frac{1}{5} \uparrow \% \quad 20\%$
--	--------------------------------------

Problem

A mining company extracts 5000 tons of ore with a concentration of metal of 3%, and 7300 tons with a concentration of 2.3%. On the basis of these two extraction figures, what is the total quantity of metal obtained?

If one ton of metal is worth \$280, what is the total value of the metal extracted?

3 [%] [x] 5000 [enter]	$3\% \times 5000 \quad 150$
[+] 2.3 [%] [x] 7300 [enter]	$3\% \times 5000 \quad 150$ $\text{ans} + 2.3\% \times 7300 \quad 317.9$
[x] 280 [enter]	$3\% \times 5000 \quad 150$ $\text{ans} + 2.3\% \times 7300 \quad 317.9$ $\text{ans} \times 280 \quad 89012$

The two extractions represent a total of 317.9 tons of metal for a total value of \$89,012.

$x10^n$ Key

[$x10^n$]

[$x10^n$] is a shortcut key to enter a number in scientific notation format.

Example

2 [$x10^n$] 5 [enter]	$2 \times 10^5 \quad 200000$
[mode] \downarrow \uparrow [enter]	$\text{MODE} \quad \text{SCI} \quad \text{DEG}$ $\text{MODE} \quad \text{RAD}$ $\text{MODE} \quad \text{NORM} \quad \text{FIX}$ $\text{MODE} \quad \text{0} \quad \text{1} \quad \text{2} \quad \text{3} \quad \text{4} \quad \text{5} \quad \text{6} \quad \text{7} \quad \text{8} \quad \text{9}$ $\text{MODE} \quad \text{CLASSIC} \quad \text{MODE} \quad \text{MODE} \quad \text{MODE} \quad \text{MODE} \quad \text{MODE}$

clear enter	2×10^5 2×10^5	200000 2×10^5
-------------	---------------------------------	--------------------------

Powers, Radicals, and Reciprocals

x^2	Calculates the square of a value. The TI-34 MultiView™ calculator evaluates expressions entered with x^2 from left to right in both Classic and MathPrint™ modes. Pressing $3 x^2$ calculates as $(3^2)^2 = 81$.
\wedge	Raises a value to the power indicated. If you insert an expression as the exponent, you must place it between parentheses. In Classic mode, exponentiation using \wedge is evaluated from left to right. The expression $2^{\wedge}3^{\wedge}2$ is evaluated as $(2^{\wedge}3)^{\wedge}2$, with a result of 64. In MathPrint™ mode, exponentiation using \wedge is evaluated from right to left. The expression $2^{\wedge}3^{\wedge}2$ is evaluated as $2^{\wedge}(3^{\wedge}2)$, with the result of 512.
$\sqrt{}$	Calculates the square root of a positive value.
$2^{nd} [x^{\sqrt{}}]$	Calculates the xth root of any positive value and any odd integer root of a negative value.
$2^{nd} [1/x]$	Calculates the reciprocal of a value.

Examples

$5 x^2 + 4 (\ 2 + 1)$ enter	$5^2 + 4(2 + 1)$ 89
$10 \wedge (-) 2$ enter	10^{-2} $\frac{1}{100}$
$\sqrt{} 49$ enter	$\sqrt{49}$ 7

$\sqrt{\quad}$ 3 x^2 + 2 \wedge 4 enter	$\sqrt{3^2+2^4}$ <small>DEG ++</small> 5
6 2nd $[x\sqrt{\quad}]$ 64 enter	$6\sqrt{64}$ <small>DEG ++</small> 2
$($ 2 + 6 $)$ 2nd $[1/x]$ enter	$\frac{1}{(2+6)}$ <small>DEG ++</small> $\frac{1}{8}$

Pi



$\pi \approx 3.141592653590$ for calculations.

$\pi \approx 3.141592654$ for display.

Example

π	2 \times π enter	$2 \times \pi$ <small>DEG ++</small> 2π
	$\leftarrow \rightarrow$	$\begin{array}{r} 2 \times \pi \\ 2\pi^{++} \end{array} \quad \begin{array}{r} \text{DEG ++} \\ 6.283185307 \end{array} \quad \begin{array}{r} 2\pi \\ 2\pi \end{array}$

Note: Classic mode displays calculations with π as a decimal approximation.

Problem

What is the area of a circle if the radius is 12 cm?

Reminder: $A = \pi r^2$.

π \times 12 \wedge 2 enter	$\pi \times 12^2$ <small>DEG ++</small> 144π
$\leftarrow \rightarrow$	$\begin{array}{r} \pi \times 12^2 \\ 144\pi^{++} \end{array} \quad \begin{array}{r} \text{DEG ++} \\ 452.3893421 \end{array} \quad \begin{array}{r} 144\pi \\ 144\pi \end{array}$

The area of the circle is 144π square cm. The area of the circle is approximately 452.4 square cm when rounded to one decimal place.

Angle Menu

2nd **[angle]**

2nd **[angle]** displays the choice of two submenus that enable you to specify the angle unit modifier as degrees ($^\circ$), minutes ($'$), seconds ($''$), radian (r), or convert units using **►DMS**. You can also convert between rectangular coordinate form (R) and polar coordinate form (P).

Choose an angle mode from the mode screen. You can choose from DEG (default) or RAD. Entries are interpreted and results displayed according to the angle mode setting without needing to enter an angle unit modifier.

If you specify an angle unit modifier from the Angle menu, the calculation is performed in that angle type, but the result will be given in the angle mode setting.

Examples

RAD	mode ► enter	<pre> DEG 360 RAD SCI FLOAT 0 123456789 CLASSIC [] ↓ </pre>
	clear 2nd [trig] 1 30 2nd [angle] 1] enter	<pre> RAD ++ sin(30°) 0.5 </pre>
DEG	mode enter	<pre> DEG RAD RAD SCI FLOAT 0 123456789 CLASSIC [] ↓ </pre>
$^\circ$ $'$ $''$	clear 2 [π] 2nd [angle] 4 enter	<pre> DEG ++ sin(30°) 0.5 2π° 360 </pre>
►DMS	1.5 2nd [angle] 5 enter	<pre> DEG ++ sin(30°) 0.5 2π° 360 1.5►DMS 1°30'0" </pre>

Convert polar coordinates $(r,\theta)=(5,30)$ into rectangular coordinates. Then convert rectangular coordinates $(x,y) = (3,4)$ into polar coordinates. Round the results to one decimal place.

R↔P	clear mode \leftarrow \leftarrow \rightarrow \rightarrow enter	<pre> FIX DEG MODE RAD MODE SCI FLOAT 0 1 2 3 4 5 6 7 8 9 CLASSIC 1 2 3 4 5 6 7 8 9 ↓ </pre>
	clear 2nd [angle] \rightarrow 3 5 2nd [,] 30 \rightarrow enter 2nd [angle] \rightarrow 4 5 2nd [,] 30 \rightarrow enter	<pre> FIX DEG +-+ P→Rx(5,30) 4.3 P→Ry(5,30) 2.5 </pre>
	2nd [angle] \rightarrow 1 3 2nd [,] 4 \rightarrow enter 2nd [angle] \rightarrow 2 3 2nd [,] 4 \rightarrow enter	<pre> FIX DEG +-+ P→Rx(5,30) 4.3 P→Ry(5,30) 2.5 R→Pr(3,4) 5.0 R→Pθ(3,4) 53.1 </pre>

Converting $(r, \theta) = (5, 30)$ gives $(x, y) = (4.3, 2.5)$ and converting $(x, y) = (3, 4)$ gives $(r, \theta) = (5.0, 53.1)$.

Problem

Two adjacent angles measure $12^\circ 31' 45''$ and $26^\circ 54' 38''$ respectively. Add the two angles and display the result in DMS format. Round the results to two decimal places.



clear mode \leftarrow \leftarrow \rightarrow \rightarrow \rightarrow \rightarrow enter	<pre> FIX DEG MODE RAD MODE SCI FLOAT 0 1 2 3 4 5 6 7 8 9 CLASSIC 1 2 3 4 5 6 7 8 9 ↓ </pre>
clear 12 2nd [angle]	<pre> FIX DEG DMS R+P 12° 31' 45" ↓ </pre>
1 31 2nd [angle] 2 45 2nd [angle] 3 \rightarrow 26 2nd [angle] 1 54 2nd [angle] 2 38 2nd [angle] 3 enter	<pre> FIX DEG +-+ 12°31'45"+26°54" 39.44 </pre>
2nd [angle] 5 enter	<pre> FIX DEG +-+ 12°31'45"+26°54" 39.44 39.43972222221▶▶▶ 39°26'23" </pre>

The result is 39 degrees, 26 minutes and 23 seconds.



Problem

It is known that $30^\circ = \pi / 6$ radians. In the default mode, degrees, find the sine of 30° . Then set the calculator to radian mode and calculate the sine of $\pi / 6$ radians.

Note: Press **clear** to clear the screen between problems.

clear 2nd [trig] 1 30) enter	
mode ▷ enter clear 2nd [trig] 1 π ⏏ 6 ▷) enter	

Retain radian mode on the calculator and calculate the sine of 30° . Change the calculator to degree mode and find the sine of $\pi / 6$ radians.



2nd [trig] 1 30 2nd [angle] enter) enter	
mode enter clear 2nd [trig] 1 π ⏏ 6 ▷ 2nd [angle] 4) enter	

Trigonometry

2nd **[trig]**

2nd **[trig]** displays a menu of all supported trigonometric functions (\sin , \cos , \tan , \sin^{-1} , \cos^{-1} , \tan^{-1}). Select the trigonometric function from the menu and then enter the value. Set the desired Angle mode before starting trigonometric calculations.

Example Degree mode

Tan	mode enter ⏏ ⏏ enter clear 2nd [trig] 3 45) enter	
Tan ⁻¹	2nd [trig] 6 1) enter	

Cos	5 \times 2nd [trig] 2 60 \rightarrow enter	5 * cos(60) 2.5
-----	---	-----------------

Example Radian mode

Tan	mode \rightarrow enter clear 2nd [trig] 3 π \rightarrow 4 \rightarrow \rightarrow enter	$\tan\left(\frac{\pi}{4}\right)$ 1
-----	--	------------------------------------

Tan ⁻¹	2nd [trig] 6 1 \rightarrow enter	$\tan^{-1}(1)$ 0.785398163
-------------------	---------------------------------------	-------------------------------

	\leftrightarrow	0.785398163 0.7853981633975+ $\frac{\pi}{4}$
--	-------------------	--

Cos	5 \times 2nd [trig] 2 π \rightarrow 4 \rightarrow \rightarrow enter	5 * cos($\frac{\pi}{4}$) 3.535533906
-----	---	---

Problem

Find angle A of the right triangle below. Then calculate angle B and the length of the hypotenuse c. Lengths are in meters. Round results to one decimal place.


Reminder:

$$\tan A = \frac{7}{3} \text{ therefore } m\angle A = \tan^{-1}\left(\frac{7}{3}\right)$$

$$m\angle A + m\angle B + 90^\circ = 180^\circ$$

$$\text{therefore } m\angle B = 90^\circ - m\angle A$$

$$c = \sqrt{3^2 + 7^2}$$



mode enter \leftarrow \leftarrow \rightarrow \rightarrow enter clear 2nd [trig] 6 7 \rightarrow 3 \rightarrow \rightarrow enter	FIN DEG ++ $\tan^{-1}\left(\frac{7}{3}\right)$ 66.8
--	--

90 \square \square 2nd \square [ans] \square enter	<table border="1"> <tr> <td>FIX</td> <td>DEG</td> <td>↔</td> </tr> <tr> <td>$\tan^{-1}\left(\frac{7}{3}\right)$</td> <td>66.8</td> <td></td> </tr> <tr> <td>90-ans</td> <td>23.2</td> <td></td> </tr> </table>	FIX	DEG	↔	$\tan^{-1}\left(\frac{7}{3}\right)$	66.8		90-ans	23.2				
FIX	DEG	↔											
$\tan^{-1}\left(\frac{7}{3}\right)$	66.8												
90-ans	23.2												
$\sqrt{\square}$ 3 \square \square \square + 7 \square \square enter	<table border="1"> <tr> <td>FIX</td> <td>DEG</td> <td>↔</td> </tr> <tr> <td>$\tan^{-1}\left(\frac{4}{3}\right)$</td> <td>66.8</td> <td></td> </tr> <tr> <td>90-ans</td> <td>23.2</td> <td></td> </tr> <tr> <td>$\sqrt{3^2+7^2}$</td> <td>7.6</td> <td></td> </tr> </table>	FIX	DEG	↔	$\tan^{-1}\left(\frac{4}{3}\right)$	66.8		90-ans	23.2		$\sqrt{3^2+7^2}$	7.6	
FIX	DEG	↔											
$\tan^{-1}\left(\frac{4}{3}\right)$	66.8												
90-ans	23.2												
$\sqrt{3^2+7^2}$	7.6												

To one decimal place, the measure of angle A is 66.8° , the measure of angle B is 23.2° , and the length of the hypotenuse is 7.6 meters.

Logarithms and Exponential Functions

\square 2nd \square [log]

\square 2nd \square [log] displays two submenus containing the functions **log**, **10[^]**, **ln**, and **e[^]**. Select the submenu, the desired log function, then enter the value and close the expression with \square \square enter.

- **log** yields the common logarithm of a number.
- **10[^]** raises 10 to the power you specify.
- **ln** yields the logarithm of a number to the base of e ($e \approx 2.718281828459$).
- **e[^]** raises e to the power you specify.

Examples

LOG	\square 2nd \square [log] 1 1 \square \square enter	<table border="1"> <tr> <td></td> <td>DEG</td> <td>↔</td> </tr> <tr> <td>log(1)</td> <td>0</td> <td></td> </tr> </table>		DEG	↔	log(1)	0				
	DEG	↔									
log(1)	0										
10 [^]	\square 2nd \square [log] 2 \square 2nd \square [log] 1 2 \square \square enter \square 2nd \square [log] 1 \square 2nd \square [log] 2 5 \square \square \square enter	<table border="1"> <tr> <td></td> <td>DEG</td> <td>↔</td> </tr> <tr> <td>$10^{\log(2)}$</td> <td>2</td> <td></td> </tr> <tr> <td>$\log(10^5)$</td> <td>5</td> <td></td> </tr> </table>		DEG	↔	$10^{\log(2)}$	2		$\log(10^5)$	5	
	DEG	↔									
$10^{\log(2)}$	2										
$\log(10^5)$	5										
LN	\square 2nd \square [log] \square 1 5 \square \square \square 2 \square enter	<table border="1"> <tr> <td></td> <td>DEG</td> <td>↔</td> </tr> <tr> <td>log(1)</td> <td>0</td> <td></td> </tr> <tr> <td>$\ln(5) \times 2$</td> <td>3.218875825</td> <td></td> </tr> </table>		DEG	↔	log(1)	0		$\ln(5) \times 2$	3.218875825	
	DEG	↔									
log(1)	0										
$\ln(5) \times 2$	3.218875825										
e [^]	\square 2nd \square [log] \square 2 .5 \square enter	<table border="1"> <tr> <td></td> <td>RAD</td> <td>↔</td> </tr> <tr> <td>$e^{.5}$</td> <td>1.648721271</td> <td></td> </tr> </table>		RAD	↔	$e^{.5}$	1.648721271				
	RAD	↔									
$e^{.5}$	1.648721271										

Statistics

2nd **[stat]** **[data]**

2nd **[stat]** displays a menu with the following options:

- **1-Var Stats** analyzes data from 1 data set with 1 measured variable, x .
- **2-Var Stats** analyzes paired data from 2 data sets with 2 measured variables— x , the independent variable, and y , the dependent variable.
- **StatVars** displays a secondary menu of statistical variables. The StatVars menu only appears after you have calculated 1-Var or 2-Var stats. Use \odot and \ominus to locate the desired variable, and press **[enter]** to select it.

Variables	Definition
n	Number of x or (x,y) data points.
\bar{x} or \bar{y}	Mean of all x or y values.
s_x or s_y	Sample standard deviation of x or y .
σ_x or σ_y	Population standard deviation of x or y .
Σx or Σy	Sum of all x or y values.
Σx^2 or Σy^2	Sum of all x^2 or y^2 values.
Σxy	Sum of $(x...y)$ for all xy pairs.
a	Linear regression slope.
b	Linear regression y -intercept.
r	Correlation coefficient.
x' (2-Var)	Uses a and b to calculate predicted x value when you input a y value.
y' (2-Var)	Uses a and b to calculate predicted y value when you input an x value.

To define statistical data points:

1. Enter data in L1, L2, or L3. (See Data Editor and List Conversions.)
2. Press **2nd** **[stat]**. Select **1-Var** or **2-Var** and press **[enter]**.
3. Select L1, L2, or L3, and the frequency.
4. Press **[enter]** to display the menu of variables.
5. To clear data, press **[data]** **[data]**, select a list to clear, and press **[enter]**.







Examples

1-Var: Find the mean of {45,55,55,55}

Clear all data	[data] [data] \downarrow \downarrow \downarrow	
Data	[enter] 45 \downarrow 55 \downarrow 55 \downarrow 55 \downarrow [enter]	
Stat	[2nd] [stat]	
	1 \downarrow \downarrow	
	[enter]	
Stat Var	[2nd] [quit] [2nd] [stat] 3	
	2 [enter]	
	\times 2 [enter]	

2-Var: Data: (45,30), (55,25); Find: $x'(45)$

Clear all data	[data] [data] \downarrow \downarrow \downarrow	
----------------	---	--


Data	enter 45 \leftarrow 55 \leftarrow \leftarrow 30 \leftarrow 25 \leftarrow	
Stat	2nd [stat] (Your screen may not show 3:StatVars if you did not previously perform a calculation.)	
	2 \leftarrow \leftarrow	
	enter	
	2nd [quit] 2nd [stat] 3 \leftarrow \leftarrow	
	enter 45] enter	







 **Problem**

For her last four exams, Ada earned the following scores.

Test No.	1	2	3	4
Score	73	94	85	78

- Find Ada's average grade on the four exams.
- Ada found an error in the two of her test scores. Test 2 was changed to 88 and Test 4 was changed to 84. Find Ada's new average grade of the four exams.
- What do you notice about Ada's average grades before the point change and after the point change?

Clear all data	data data 4	
-------------------	----------------------------------	---

Data	73 ↻ 94 ↻ 85 ↻ 78 ↻	
	2nd [stat]	
	1 ↻ ↻ enter The average grade is 82.5.	
	data ↻ 88 ↻ ↻ 84 ↻ ↻	
	2nd [stat] 1	
	↻ ↻ enter The new average grade is 82.5.	

Ada's average did not change. It remained 82.5 after the grade corrections.

The reason the average did not change is that Test 2 had a decrease of 6 points while Test 4 had an increase of 6 points. Overall, the total points for all four tests remained the same (330 points).

Problem

The table below gives the results of a braking test.

Test No.	1	2	3	4
Speed (kph)	33	49	65	79
Distance (m)	5.30	14.45	20.21	38.45

Using the relationship between these data points, estimate the stopping distance required for a vehicle traveling at 55 kph.

A hand-drawn scatter plot of these data points suggest a linear relationship. The TI-34 MultiView™ calculator uses the least squares method to find the line of best fit, $y' = ax' + b$, for data entered in lists.

data data 4	<pre> DEG [2nd][F1] CNVRSN 2:Clear L2 3:Clear L3 4:Clear ALL </pre>
33 \ominus 49 \ominus 65 \ominus 79 \ominus 5.3 \ominus 14.45 \ominus 20.21 \ominus 38.45 \ominus	<pre> 0 0 0 + 49 14.45 65 20.21 79 38.45 ----- L2(5)= </pre>
2nd [stat]	<pre> STATS 1:1-Var Stats 2:2-Var Stats </pre>
2 \ominus \ominus	<pre> 2-VAR STATS XDATA: [L2] L2 L3 YDATA: [L1] L3 CALC </pre>
enter	<pre> 2-Var: [L1] L2 n=4 2: x=56.5 3: Sx=19.89137166 </pre>
Press \ominus to view a and b .	<pre> DEG 2-Var: [L1] L2 C1: xy=5234.15 D: a=0.6773251896 E: b=-18.66637321 </pre>

This line of best fit, $y' = 0.6773251896x' - 18.66637321$ models the linear trend of the data.

2nd [quit] 2nd [stat] 3 \ominus	<pre> 2-Var: [L1] L2 F1: r=0.963411717 G: x' H: y' </pre>
enter 55 \square enter	<pre> DEG ++ y'(55) 18.58651222 </pre>

The linear model gives an estimated braking distance of 18.59 meters for a vehicle traveling at 55 kph.

Probability

prb

This key displays two menus: **PRB** and **RAND**.





PRB contains the following options:

nPr	Calculates the number of possible permutations of n items taken r at a time, given n and r . The order of objects is important, as in a race. n and r must be positive integers.
nCr	Calculates the number of possible combinations of n items taken r at a time, given n and r . The order of objects is not important, as in a hand of cards. n and r must be positive integers.
!	A factorial is the product of the positive integers from 1 to n . n must be a whole number ≤ 69 .

RAND contains the following options:

rand	Generates a random real number between 0 and 1. To control a sequence of random numbers, store an integer (seed value) ≥ 0 to rand . The seed value changes randomly every time a random number is generated.
randint(Generates a random integer between 2 integers, A and B , where $A \leq \text{randint} \leq B$. Separate the 2 integers with a comma.

Examples

nPr	8	
	[prb]	
	[enter] 3 [enter]	
nCr	52 [prb] 25 [enter]	

!	4 prb 3 enter	4! 24
STO ▶ rand	5 sto▶ prb ↓	PRB 2:RAND 1:rand 2:randint(
	1 enter	5→rand 5
rand	prb ↓ 1 enter	5→rand 5 rand 0.000093165
randint(prb ↓ 2 3 2nd [,] 5) enter	5→rand 5 rand 0.000093165 randint(3,5) 5

Problem

An ice cream store advertises that it makes 25 flavors of home made ice cream. You like to order three different flavors in a dish. How many combinations of ice cream can you test out over a very hot summer?

25	25
prb 2	25 nCr
3 enter	25 nCr 3 2300

You can choose from 2300 dishes with different combinations of flavors! If a long hot summer is about 90 days long, you will need to eat about 25 ice cream dishes each day!

Math Tools

Data Editor and List Conversions






data

data lets you enter data in up to 3 lists. Each list can contain up to 42 items. Press **2nd** \uparrow to go to the top of a list, and **2nd** \downarrow to go to the bottom of a list.

List conversions accept $f \leftrightarrow d$, $\%$, \rightarrow Simp, and $n/d \leftrightarrow Un/d$.

Numeric notation, decimal notation, and angle modes affect the display of an element (except fractional elements).

Example

L1	data 1 $\frac{1}{4}$ 4 \downarrow 2 $\frac{1}{4}$ 4 \downarrow 3 $\frac{1}{4}$ 4 \downarrow 4 $\frac{1}{4}$ 4 enter	
Conversion	\rightarrow data \rightarrow	
	enter	
	data enter 2nd $[f \leftrightarrow d]$	
	enter	

Notice L2 is calculated per the conversion you entered, and L2(1)= in the author line is highlighted to indicate the list is the result of a conversion.







 **Problem**

1 2 3

Find the decimal representation of $\frac{1}{9}$, $\frac{2}{9}$, and $\frac{3}{9}$. From this pattern, can you

7

predict the decimal representation for $\frac{7}{9}$? Check your answer using the lists on the calculator.

<p>data data 4 data \rightarrow 5</p>	
<p>1 $\frac{1}{9}$ \rightarrow 2 $\frac{2}{9}$ \rightarrow 3 $\frac{3}{9}$ enter</p>	
<p>\rightarrow data \rightarrow 1</p>	
<p>data 1 2nd [f\leftrightarrowd]</p>	
<p>enter</p>	
<p>Input the rest of the fractions to test your pattern. Notice L2 updates as you enter in L1.</p>	

The pattern appears to show that the decimal representation is a repetition of the

4 5 6 7

number in the numerator for ninths. Entering $\frac{4}{9}$, $\frac{5}{9}$, $\frac{6}{9}$ and finally $\frac{7}{9}$ validates that statement. Notice the last digit in the list is rounded, so $0.777777\dots$ is shown rounded to 0.77778 .

Stored Operations (op)

op1 **op2** **2nd** [set op1] **2nd** [set op2]

The TI-34 MultiView™ calculator stores two operations, **op1** and **op2**. To store an operation to **op1** or **op2** and recall it:

1. Press **2nd** [set op1] or **2nd** [set op2]. You may have to press **clear** if a previous operation is displayed.
2. Enter the operation (any combination of numbers, operations, or menu items and their arguments).
3. Press **enter** to save the operation to memory.
4. **op1** or **op2** recalls and displays the operation on the entry line. The TI-34 MultiView™ calculator automatically calculates the result (without pressing **enter**).

Examples

Set op1	2nd [set op1] × 2 + 3 enter	$OP1 = *2+3$ <small>PRD</small>
op1	4 op1	$4 * 2 + 3$ <small>DEG</small> <small>++</small> $n=1$ 11
	6 op1	$4 * 2 + 3$ <small>DEG</small> <small>++</small> $n=1$ 11 $6 * 2 + 3$ $n=1$ 15
Set op2	2nd [set op2] × 10 enter	$OP2 = *10$ <small>PRD</small>
op2	1 op2	$1 * 10$ <small>DEG</small> <small>++</small> $n=1$ 10
	op2	$1 * 10$ <small>DEG</small> <small>++</small> $n=1$ 10 $10 * 10$ $n=2$ 100
	op2	$1 * 10$ <small>DEG</small> <small>++</small> $n=1$ 10 $10 * 10$ $n=2$ 100 $100 * 10$ $n=3$ 1000

Problem

Harry's father will pay him \$15 per week if he helps out a few hours at his family's grocery store. Harry would like to save all he earns to buy several of his favorite books and video games. He estimates that he will need to earn \$240 to buy everything he would like to have. Create a table of Harry's weekly earnings to see how his savings will grow. How many weeks will Harry need to work to save enough money for his purchases?

<p>2nd [set op1] (Press clear if necessary to clear a previous operation) + 15 enter</p>	<p>OP1=+15 RAD</p>															
<p>0 [op1] [op1] [op1] [op1]</p>	<table border="1"> <thead> <tr> <th></th> <th>DEG</th> <th>↔</th> </tr> </thead> <tbody> <tr><td>0+15</td><td>n=1</td><td>15</td></tr> <tr><td>15+15</td><td>n=2</td><td>30</td></tr> <tr><td>30+15</td><td>n=3</td><td>45</td></tr> <tr><td>45+15</td><td>n=4</td><td>60</td></tr> </tbody> </table>		DEG	↔	0+15	n=1	15	15+15	n=2	30	30+15	n=3	45	45+15	n=4	60
	DEG	↔														
0+15	n=1	15														
15+15	n=2	30														
30+15	n=3	45														
45+15	n=4	60														
<p>[op1] [op1] [op1] [op1]</p>	<table border="1"> <thead> <tr> <th></th> <th>DEG</th> <th>↔</th> </tr> </thead> <tbody> <tr><td>60+15</td><td>n=5</td><td>75</td></tr> <tr><td>75+15</td><td>n=6</td><td>90</td></tr> <tr><td>90+15</td><td>n=7</td><td>105</td></tr> <tr><td>105+15</td><td>n=8</td><td>120</td></tr> </tbody> </table>		DEG	↔	60+15	n=5	75	75+15	n=6	90	90+15	n=7	105	105+15	n=8	120
	DEG	↔														
60+15	n=5	75														
75+15	n=6	90														
90+15	n=7	105														
105+15	n=8	120														
<p>[op1] [op1] [op1] [op1]</p>	<table border="1"> <thead> <tr> <th></th> <th>DEG</th> <th>↔</th> </tr> </thead> <tbody> <tr><td>120+15</td><td>n=9</td><td>135</td></tr> <tr><td>135+15</td><td>n=10</td><td>150</td></tr> <tr><td>150+15</td><td>n=11</td><td>165</td></tr> <tr><td>165+15</td><td>n=12</td><td>180</td></tr> </tbody> </table>		DEG	↔	120+15	n=9	135	135+15	n=10	150	150+15	n=11	165	165+15	n=12	180
	DEG	↔														
120+15	n=9	135														
135+15	n=10	150														
150+15	n=11	165														
165+15	n=12	180														
<p>[op1] [op1] [op1] [op1]</p>	<table border="1"> <thead> <tr> <th></th> <th>DEG</th> <th>↔</th> </tr> </thead> <tbody> <tr><td>180+15</td><td>n=13</td><td>195</td></tr> <tr><td>195+15</td><td>n=14</td><td>210</td></tr> <tr><td>210+15</td><td>n=15</td><td>225</td></tr> <tr><td>225+15</td><td>n=16</td><td>240</td></tr> </tbody> </table>		DEG	↔	180+15	n=13	195	195+15	n=14	210	210+15	n=15	225	225+15	n=16	240
	DEG	↔														
180+15	n=13	195														
195+15	n=14	210														
210+15	n=15	225														
225+15	n=16	240														

The table of values of Harry's weekly earnings is shown on the screens. From this table, we can read that Harry will have to work 16 weeks to earn \$240.

Reference Information

Errors

When the TI-34 MultiView™ calculator detects an error, it returns an error message with the type of error.

To correct the error, note the error type and determine the cause of the error. If you cannot recognize the error, use the following list, which describes error messages in detail.

Press **clear** to clear the error message. The previous screen is displayed with the cursor at or near the error location. Correct the expression.

ARGUMENT — A function does not have the correct number of arguments.

DIVIDE BY 0 — You attempted to divide by 0.

DOMAIN — You specified an argument to a function outside the valid range. For example:

- For $x\sqrt{y}$: $x = 0$ or ($y < 0$ and x is not an odd integer).
- For \sqrt{x} : $x < 0$.
- For **LOG** or **LN**: $x \leq 0$.
- For **tan**: $x = 90^\circ, -90^\circ, 270^\circ, -270^\circ, 450^\circ$, etc., and equivalent for radian mode.
- For \sin^{-1} or \cos^{-1} : $|x| > 1$.
- For **nCr** or **nPr**: n or r are not integers ≥ 0 .
- For **simp**: Entering a simplify value of 0; using a simplify value of $\geq 1E10$; attempting to simplify non-fractions.

EQUATION LENGTH — An entry exceeds the digit limits (88 for entry line and 47 for stat entries or constant entries); for example, combining an entry with a constant that exceeds the limit.

FRQ DOMAIN — FRQ value (in 1-var statistics) < 0 .

OVERFLOW — You attempted to enter, or you have calculated, a number that is beyond the range of the calculator.

STAT — Attempting to calculate 1-var or 2-var stats with no defined data points, or attempting to calculate 2-var stats when the data lists are not of equal length.

CONVERSION

- The conversion does not contain a list name (L1, L2, or L3) followed by a conversion (for example, $f \leftrightarrow d$).
- You attempted to enter a function (for example, $L1 + 3$).

SYNTAX — The command contains a syntax error, or has misplaced functions, arguments, parentheses, or commas. If using $\frac{\square}{\square}$, try using $\frac{\square}{\square}$.

OP NOT DEFINED — Operation (**op1** or **op2**) is not defined.

MEMORY LIMIT

- The calculation contains too many pending operations (more than 23).
- If using **op1** or **op2**, you attempted to enter more than four levels of nested functions using fractions, square roots, exponents with \wedge , $x\sqrt{\quad}$, and x^2 (MathPrint™ mode only).

LOW BATTERY — Replace the battery

Note: This message displays briefly and then disappears. Pressing clear does not clear this message.

Battery Information

Battery precautions

- Do not leave batteries within the reach of children.
- Do not mix new and used batteries. Do not mix brands (or types within brands) of batteries.
- Do not mix rechargeable and non-rechargeable batteries.
- Install batteries according to polarity (+ and -) diagrams.
- Do not place non-rechargeable batteries in a battery recharger.
- Properly dispose of used batteries immediately.
- Do not incinerate or dismantle batteries.
- Seek medical advice immediately if a cell or battery has been swallowed. In the USA, contact the National Capital Poison Center collect at 1-800-222-1222.

Battery disposal

Do not mutilate, puncture, or dispose of batteries in fire. The batteries can burst or explode, releasing hazardous chemicals. Discard used batteries according to local regulations.

Per CA Regulation 22 CCR 67384.4, the following applies to the button cell battery in this unit:

Perchlorate Material - Special handling may apply.

See www.dtsc.ca.gov/hazardouswaste/perchlorate

How to remove or replace the battery

The TI-34 MultiView™ calculator uses one 3 volt CR2032 lithium battery.

Remove the protective cover and turn the TI-34 MultiView calculator face downwards.

- With a small screwdriver, remove the screws from the back of the case.
- From the bottom, carefully separate the front from the back. **Be careful** not to damage any of the internal parts.
- With a small screwdriver (if required), remove the battery.

- To replace the battery, check the polarity (+ and -) and slide in a new battery. Press firmly to snap the new battery into place.

Important: When replacing the battery, avoid any contact with the other components of the TI-34 MultiView calculator.

Dispose of the dead battery immediately and in accordance with local regulations.

In Case of Difficulty

Review instructions to be certain calculations were performed properly.

Check the battery to ensure that it is fresh and properly installed.

Change the battery when:

- does not turn the unit on, or
- The screen goes blank, or
- You get unexpected results.

General Information

Online Help

education.ti.com/eguide

Select your country for more product information.

Contact TI Support

education.ti.com/ti-cares

Select your country for technical and other support resources.

Service and Warranty Information

education.ti.com/warranty

Select your country for information about the length and terms of the warranty or about product service.

Limited Warranty. This warranty does not affect your statutory rights.

Texas Instruments Incorporated

12500 TI Blvd.

Dallas, TX 75243